



Product certificate K6266/03

Issued 2018-10-01

Replaces 2007-07-01

Page 1 of 3

Sanitary tapware; single taps and mixer taps

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Vola a/s

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K652/03 "Sanitary tapware; single taps and mixer taps" dated d.d. 01-02-2012.

which covers the requirements of

EN 200:2008

"Sanitary tapware: Single taps and combination taps for water supply systems of type 1 and type 2 – General technical specification".

Luc Leroy
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

Vola a/s
Lunavej 2
8700 HORSENS
Denemarken
Tel. +45 7023.5500
Fax. +45 70235511
E-mail sales@vola.dk
Internet www.vola.dk

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Sanitary tapware; single taps and mixer taps

Technical specification**The products mentioned below belong to this certificate**

Showermixer

600 – combination, concealed with diverter

700 -- combination, concealed

800 -- combination, concealed with diverter

1500 -- combination, concealed

1641 T8 – with diverter

1671

Sinkmixer

KV 3,

KV 4,

KV 6

KV 7.

Basinmixer

HV 5,

HV 6

HV 7.

Bathmixer

1611

1621

Single taps

S 50,

RB 1

RB 4

900 - combination, concealed

Sanitary tapware; single taps and mixer taps

Application and use

The sanitary taps "single taps and mixer taps" are intended for application in drinking water installations with a static waterpressure of maximum 1000 kPa, a minimum dynamic pressure of 50 kPa and a maximum watertemperature of 90°C.

The recommended limits for correct operation are a dynamic pressure between 100 kPa and 500 kPa and a water temperature of maximum 65°C.

Marking

The products are marked with the wordmark "KIWA" and the abbreviated wordmark "KK" in a rectangle.

Place of the mark:

- "KIWA" on the taphouse,
- "KK" on the headpart(s).

Additional compulsory specifications:

- name or mark of manufacturer: on the taphouse an headpart(s);
- indication for the watertemperature: on the controlknobs;
- identification of the accoustic group if classified, on the body;
- identification of the flow resistance class, on the body.

Method of marking:

- Non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- **the supplier has delivered in accordance with the agreement;**
- **the mark and the marking method are correct;**
- **the products show no visible defects as a result of transport etc.**

If you should reject a product on the basis of the above, please contact:

- **Vola a/s**

and, if necessary,

- **Kiwa Nederland B.V.**

Consult the supplier's processing guidelines for the proper storage and transport methods.